

Station Name: 631 20 01

Horizontal Datum: NAD 83/91
Vertical Datum: NAVD 88
Control Point ID: Book: 631

Page: 20 Pt #: 1

State: Washington
County: Snohomish
Established By: C of E

Section: 34

Township: 29 N

Range: 4 E

LATITUDE: 47 57 18.86995
LONGITUDE: 122 16 10.93355

ORTHOMETRIC HEIGHT: 198.1 Feet
60.37 Meters

Washington State Plane Coordinates - North Zone

	Northing	Easting	Point Scale Factor (to 9 decimal places)	Convergence Deg Min Sec
Feet	351727.267	1288480.553	0.999946267	-01 04 09.9
Meters	107206.6854	392729.6580		

HORIZONTAL DATA:

Horizontal position established by: LEICA radial rapid static GPS survey and LEICA SKI adjustment software.

Relative point position accuracy: 0.02 ft. N and 0.01 E @ 1 sigma (unconstrained), and 0.03 ft. N & 0.02 ft. E @ 1 sigma, constrained to City Points, E052 & S137

Surveyor's estimated cumulative position accuracy 0.05 ft. @ 1 sigma.

Vertical Data:

Vertical position established by: LEICA radial rapid static GPS survey and LEICA SKI adjustment software.

Relative point position accuracy: 0.03 ft. @ 1 sigma (unconstrained), and 0.06 ft. @ 1 sigma constrained to City point, E052 & S137.

Surveyor's estimated cumulative relative positional accuracy: 0.1 ft. @ 1 sigma.

Correction to NGVD 29:=- 1.122 m .

Data sheet edited by Geodetic Consultants 1996.

Revised by Geodetic Consultants 5/5/1997.

MONUMENT DESCRIPTION

A 4 inch diameter iron pipe with a concrete plug and copper tack in an iron monument box that is 2 inches below the surrounding asphalt surface.

TO REACH

Located on Taylor Drive about 240 ft east of Baker Drive.

REFERENCES

Az from North	Distance	Reference Description
184 degrees	14.0 ft	from a utility pole
358 degrees	18.0 ft	from a utility pole
288 degrees	57.2 ft	from the mailbox at house number 2705

Month & Year Recovered :

Condition of Mark:

Recovered By: